PRODUCT DATASHEET





Model

SMART 100 - 3.8 Watts & 21dBA

Description

100mm high efficient wall / ceiling exhaust air fan with built in variable timer, humidity sensor, speed controller and a remote control

Application


Residential premises / Toilets / Bathrooms / Laundries / Ensuites

Technical specification

Voltage [V/50 Hz]	220-240 DC		
Power [W]	17-19		
Extract capacity [m³/h]	33-133		
Noise level 3m [dBA]	17-32		
r.p.m.	Variable		
Installation type	Surface		
Installation site	Wall / Ceiling		
Installation position	Any		
DN (diameter nominal) [mm]	100-125		
Air flow temperature [°C]	-10 - +45		
Index of protection	IP 44		
Casing material	ABS plastic		
Front panel material	ABS plastic		
Impeller material	ABS plastic		
Colour	White		

HUMIDITY TIMER SPEED 24 HOURS WODE SWITCH DELAY QUIET MAXIMAL 5 15 30 STATUS

Dimensions [mm]



Туре	Dimensions [mm]				
	а	b	С	d	е
Smart 100	155	209	28	98	28

Ventilation Solutions Australia (VSA) is not responsible for mistakes or printing errors and retain the right to make technical modifications without giving prior notice.



